



MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s):
17-111-11

Product Name: ELASTIBITE

Release Date: March 10, 2006

1. Product and Company Identification

| | |
|--|---|
| Trade Name & Synonyms GAC Elastibite | MSDS Code Number GAC-BITE |
| Chemical Name Ethylene-vinyl acetate copolymer | Manufacture / Distributor GAC International Inc. |
| C.A.S. Number 24937-78-8 | Address 355 Knickerbocker Ave. Bohemia, NY USA 11716 |
| Grades or Minor Variant Identities NA | Information Telephone Number 1-631-419-1700 |
| Product Use (for Canada) NA | Emergency Telephone Number 1-631-419-1700 |

2. Composition of Ingredients

| Hazardous Components | C.A.S. Number | Exposure Limits | % |
|---|---------------|-----------------|----|
| Ethylene vinyl acetate copolymer | 24937-78-8 | NA | NA |
| Ingredient name: Escorene Ultra LD 723 The composition of this mixture may be proprietary information. In the event of medical emergency, compositional information will be provided to a physician or nurse. This product is hazardous as defined in 29 CFR 1910.1200, based on the following compositional information. OSHA HAZARD COMPONENT ACGIH/TLV Vinyl acetate Possible human carcinogen Vinyl acetate | | | |

3. Hazard Identification

| Emergency Overview | | | | | |
|--------------------|---|---|-----------------------------------|------------------------------------|-----------------|
| Routes of Exposure | Signs and Symptoms | Single, Repeated, or Lifetime Exposure | Severity (Mild, Moderate, Severe) | Acute and Chronic Health Effect(s) | Target Organ(s) |
| Eye | Particulates may scratch eye surfaces/cause mechanical irritation. | NA | NA | NA | NA |
| Skin | Negligible hazard at ambient temperatures (-18 to 38 deg C; 0-100 deg F) | Exposure to hot material may cause thermal burns. | NA | NA | NA |
| Inhalation | Negligible hazard at ambient temperature (-18 to 38 deg c; 0-100 deg F). Vapors and/or aerosols, which may be formed at elevated temperatures, may be irritating to eyes and respiratory tract. | NA | NA | NA | NA |
| Ingestion | Minimal toxicity. | NA | NA | NA | NA |
| Other | Chronic effects: This product contains vinyl acetate monomer. No carcinogen effects were observed in long-term drinking water studies in rats. Drinking water studies in rats. Long-term inhalation of this chemical at air conditions of 600 PPM produces nasal tremors in rats. Mice exposed to the same condition were not affected. | NA | NA | NA | NA |



MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s):
17-111-11

Product Name: ELASTIBITE

Release Date: March 10, 2006

Medical Conditions Aggravated by Exposure

NA

Carcinogenicity (IARC, NTP)

The international agency for research on cancer (IARC) evaluated vinyl acetate in 1995 and found it to be a possible human carcinogen, classification 2B. The American conference of governmental industrial hygienists (ACGIH) has evaluated vinyl acetate and found it to be a group A3, animal carcinogen. The ACGIH also reported that available evidence suggests that the agent is not likely to cause cancer in humans at the recommended exposure levels.

Potential Environmental Effects

NA

4. First Aid Measures

| Routes of Exposure | First Aid Instructions | Immediate Medical Attention | Delayed Effects |
|--|---|------------------------------------|-----------------|
| Eye | This product is an inert solid. If in eye, remove as one would any foreign object. | NA | NA |
| Skin | For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention. No attempt should be made to remove materials from skin or to remove contaminated clothing, as the damaged flesh can be easily torn. | Get prompt medical attention. | NA |
| Inhalation | In case of adverse exposure to vapors/ or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. | Call for prompt medical attention. | NA |
| Ingestion | First aid is normally not required. | NA | NA |
| Other | NA | NA | NA |
| Note to Physicians (Treatment, Testing, and Monitoring) | | | |
| NA | | | |

5. Fire and Explosion Data

| | | | |
|--|--|---|--|
| Flashpoint & Method: °C /649 °F Note: Estimated, greater than. | Flammable (Explosive) Limits in Air LEL: N/A UEL: N/A | Autoignition Temperature N/A | Other General hazard: Solid material may burn at or above flashpoint, and airborne dust may explode if ignited. Toxic gases will form upon combustion. Static discharge, material can accumulate static charges, which can cause in incendiary electrical discharge. |
| Flame Propagation or Burning NA | Properties Contributing to Fire Intensity NA | Flammability Classification Health- , Flammability- , Reactivity-NA | |
| Extinguishing Media NA | | Extinguishing Media to Avoid NA | |
| Protection and Procedures for Firefighters Use water spray to cool fire-exposed surfaces, protect personnel, and extinguish the fire. Respiratory and eye protection required for fire fighting personnel. | | | |
| Unusual Fire and Explosion Hazards Decomposition products under fire conditions: Oxygen-lean conditions may produce carbon monoxide and irritating smoke, acetic acid. | | | |



MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s):
17-111-11

Product Name: ELASTIBITE

Release Date: March 10, 2006

6. Accidental Release Measures

| |
|--|
| <p>Containment Techniques</p> <p>Land spill: Recover spilled material and place in suitable containers for recycle or disposal. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.</p> |
| <p>Spill/Leak Clean-Up Procedures and Equipment</p> <p>Water spill: Plastic pellets are defined by the USA EPA under the clean water act (40 CFR 122.26) as a “ significant material” which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other clean water act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties. Skim from surface. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Recover the spilled material and place in suitable containers for recycle or disposal.</p> |
| <p>Evacuation Procedures</p> <p>NA</p> |
| <p>Special Instructions</p> <p>NA</p> |
| <p>Reporting Requirements</p> <p>NA</p> |

7. Handling and Storage

| |
|---|
| <p>Handling Practices and Warnings</p> <p>Electrostatic accumulation handling: Yes, use proper bonding and/or grounding procedure.</p> |
| <p>Storage Practices and Warnings</p> <p>Storage temperature: Deg F Ambient. Loading/unloading temperature: Deg F Ambient. Storage/ Transport pressure, MMHG: Atmospheric. Loading/unloading viscosity, CST: Solid.</p> <p>Storage and Handling: Keep container closed. Handle and open containers with care. Store in a cool, well-ventilated place away from incompatible materials. Do not handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight. Material may accumulate static charges, which may cause an electrical spark (ignition source). Use proper bonding and / or grounding procedures.</p> <p>Shelf life: 2 years.</p> |

8. Exposure Control/Personal Protection

| | | |
|--|---|--|
| <p>Ventilation</p> <p>Local exhaust ventilation of process equipment may be needed to control particulate exposures to below the recommended exposure limit.</p> | <p>Other Engineering Controls</p> <p>NA</p> | |
| <p>Routes of Entry:</p> <p>Eye/Face</p> | <p>Personal Protective Equipment (PPE) for Normal Use:</p> <p>Where contact may occur with hot material, wear face shield. Where contact is likely with open systems at ambient temperatures (-18 to 38 deg C, 0 – 100 deg F) wear safety glasses with side shields.</p> | <p>PPE for Emergencies:</p> <p>NA</p> |
| <p>Skin</p> | <p>Where contact may occur with hot material, wear thermal resistant gloves, arm protection.</p> | <p>NA</p> |
| <p>Inhalation</p> | <p>NA</p> | <p>NA</p> |
| <p>General Hygiene Considerations and Work Practices</p> <p>OSHA REGULATION 29 CF1910.1000 REQUIRES THE FOLLOWING PERMISSABLE EXPOSURE LIMITS:</p> <p>5/MG/M3 (Respirable dust), and 15/MG/M3 (Total dust) based on OSHA PEL for nuisance dust. A TWA of 10PPM (30 mg.m3) and a STEL of 20 PPM (60 mg/m3) for vinyl acetate. The recommended permissible exposure levels indicated above reflect the levels revised by OSHA in 1989 or in subsequent regulatory activity. Although the 1989 levels have since been vacated by the 11th circuit court of appeals, Exxon Mobil chemical company recommends that the lower exposure levels be observed as reasonable worker protection.</p> <p>THE ACGIH RECOMMENDS THE FOLLOWING THRESHOLD LIMIT VALUES:</p> <p>A TWA of 10/MG/M3 for inhalation particulate (total dust) and a TWA of 3 MG/M3 for respirable particulate (total dust) for particulates not otherwise classified (PNOC). A TWA of 10 PPM (35 MG/M3 and a STEL of 15 PPM (53 MG/M3) for vinyl acetate, with an A3 designation.</p> | | |
| <p>Protective Measures During Repair and Maintenance of Contaminated Equipment</p> <p>NA</p> | | |
| <p>Other Protective Measures and Equipment</p> <p>NA</p> | | |



MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s):
17-111-11

Product Name: ELASTIBITE

Release Date: March 10, 2006

9. Physical and Chemical Characteristics

| | | |
|---|---|---|
| Appearance Pellets. Color: Opaque white to transparent. | | Odor NA |
| Normal Physical State: <input type="checkbox"/> Liquid <input type="checkbox"/> Gas <input checked="" type="checkbox"/> Solid <input type="checkbox"/> _____ (Other) | | Boiling Point °C / °F N/A Melting Point 99-115 °C 210-240°F Freezing Point °C / °F |
| Specific Gravity or Density (H₂O=1) .091 - .96 | Solubility in Water Insoluble | pH NA |
| Vapor Pressure (mm Hg @ 20°C) N/A | Vapor Density (AIR= 1) NA | Evaporation Rate (Butyl Acetate = 1) NA |
| Other Viscosity of liquid: N/A | | |

10. Stability and Reactivity Data

| | |
|--|---|
| Incompatibility (Materials to Avoid) Temperatures above 300 F (150C) with fluorine. | |
| Hazardous Products Produced During Decomposition Will not occur | |
| Hazardous Polymerization? <input type="checkbox"/> May Occur <input checked="" type="checkbox"/> May Not Occur | Conditions to Avoid °C / °F N/A |
| Stability? <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable | Conditions to Avoid °C / °F N/A |

11. Toxicological Information

| |
|--|
| Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic or Reproductive Effects, or Structure Activity Data Please refer to section 3 for available information on potential health effects. |
|--|

12. Ecological Information

| |
|---|
| Toxicity, Environmental Fate, Physical/Chemical Data, or Other Data Supporting Environmental Hazard Statements No specific ecological data are available for this product. Please refer to section 6 for information regarding accidental releases and section 15 for regulatory reporting information. |
|---|

13. Disposal Considerations

| |
|--|
| Regulations Please refer to sections 5, 6, and 15 for disposal and regulatory information. |
| Properties (Physical/Chemical) Affecting Disposal NA |

14. Transport Information

| | | |
|--|---|------------------------------------|
| Regulated for shipping? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Proper Shipping Name Elastibite | Packing Group NA |
| Do changes in quantity, packaging, or shipment method change product classification? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Hazard Class NA | Identification Number NA |
| Other Not regulated under US department of transportation. | | |



MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s):
17-111-11



Product Name: ELASTIBITE

Release Date: March 10, 2006

15. Regulatory Information

Federal Regulations

CERCLA: If this product is accidentally spilled, it is not subject to any special reporting under the requirements of the comprehensive environmental response, compensation and liability act (CERCLA). We recommend you contact local authorities to determine if there may be other local reporting requirements.

SARA TITLE III: Under the provisions of title III, sections 311/312 of the superfund amendments and reauthorization act, this product is classified into the following hazard categories: Delayed health. This information may be subject to the provisions of the community right to know reporting requirements (40 CFR 370) if threshold quantity criteria are met.

This component Vinyl acetate CAS NO 108-05-4 Maximum % .2

International Regulations

NA

Other

HMIS RATINGS: Health 0 Flammability 0 Reactivity 0

NFPA 0= Minimal 1= Slight 2= Moderate 3= Serious 4= Severe

The CAS registry number for ethylene-vinyl acetate copolymer is 24937-78-8.

National Fire Protection association standards NFPA 654 and 68 indicate possible explosion hazard of dust particles. Conform accordingly. Avoid accumulation of dust or dust clouds; Operate handling and storage systems leak free, practice good housekeeping. Keep from sources of ignition. Do not store near heat, flame, or strong oxidants. Assure proper electrical grounding of all handling equipment.

Product may also contain varying levels of additives, such as slip and antiblocking agents, antioxidants, stabilizers, and corrosion inhibitors. Special precautions: Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by products, vinyl acetate and acetic acid which may be evolved at elevated temperatures. It is recommended that the current ACGIH-TLV's for these materials be observed.

16. Other Information

Supplier Number: 31/17

Supplier Release: October 6, 2003 Rev: 02

N/E = not established. N/D = not determined. N/A = not applicable.